

COMMON PIPE SIZES

DIMENSIONS SHOWN ARE TO ASME B36.10

Nominal Size		Outside Diameter mm (inch)	Wall Thickness mm	Inside Diameter mm	Plain End Mass kg/m	Identification	
NPS	⊕ DN					Standard (STD) X-Strong (XS) XX-Strong (XXS)	Schedule Number
1/8	6	10.3 (0.405)	1.73	6.8	0.37	STD	40
			2.41	5.5	0.47	XS	80
1/4	8	13.7 (0.540)	2.24	9.2	0.63	STD	40
			3.02	7.7	0.80	XS	80
3/8	10	17.1 (0.675)	2.31	12.5	0.84	STD	40
			3.20	10.7	1.10	XS	80
1/2	15	21.3 (0.840)	2.77	15.8	1.27	STD	40
			3.73	13.9	1.62	XS	80
			4.78	11.8	1.95	-	160
			7.47	6.4	2.55	XXS	-
3/4	20	26.7 (1.050)	2.87	20.9	1.69	STD	40
			3.91	18.9	2.20	XS	80
			5.56	15.5	2.90	-	160
			7.82	11.0	3.64	XXS	-
1	25	33.4 (1.315)	3.38	26.6	2.50	STD	40
			4.55	24.3	3.24	XS	80
			6.35	20.7	4.24	-	160
			9.09	15.2	5.45	XXS	-
1 1/4	32	42.2 (1.660)	3.56	35.1	3.39	STD	40
			4.85	32.5	4.47	XS	80
			6.35	29.5	5.61	-	160
			9.70	22.8	7.77	XXS	-
1 1/2	40	48.3 (1.900)	3.68	40.9	4.05	STD	40
			5.08	38.1	5.41	XS	80
			7.14	34.0	7.25	-	160
			10.15	27.9	9.55	XXS	-
2	50	60.3 (2.375)	3.91	52.5	5.44	STD	40
			5.54	49.2	7.48	XS	80
			8.74	42.9	11.11	-	160
			11.07	38.2	13.44	XXS	-
2 1/2	65	73.0 (2.875)	5.16	62.7	8.63	STD	40
			7.01	59.0	11.41	XS	80
			9.53	54.0	14.92	-	160
			14.02	45.0	20.39	XXS	-

Nominal Size		Outside Diameter mm (inch)	Wall Thickness mm	Inside Diameter mm	Plain End Mass kg/m	Identification	
NPS	⊕ DN					Standard (STD) X-Strong (XS) XX-Strong (XXS)	Schedule Number
3	80	88.9 (3.500)	5.49	77.9	11.29	STD	40
			7.62	73.7	15.27	XS	80
			11.13	66.7	21.35	-	160
3 1/2	90	101.6 (4.000)	5.74	90.1	13.57	STD	40
			8.08	85.4	18.64	XS	80
4	100	114.3 (4.500)	6.02	102.3	16.08	STD	40
			8.56	97.2	22.32	XS	80
			11.13	92.1	28.32	-	120
			13.49	87.3	33.54	-	160
			17.12	80.1	41.03	XXS	-
5	125	141.3 (5.563)	6.55	128.2	21.77	STD	40
			9.53	122.3	30.97	XS	80
			12.70	115.9	40.28	-	120
			15.88	109.6	49.12	-	160
			19.05	103.2	57.43	XXS	-
6	150	168.3 (6.625)	7.11	154.1	28.26	STD	40
			10.97	146.3	42.56	XS	80
			14.27	139.7	54.21	-	120
			18.26	131.8	67.57	-	160
			21.95	124.4	79.22	XXS	-
8	200	219.1 (8.625)	6.35	206.4	33.32	-	20
			7.04	205.0	36.82	-	30
			8.18	202.7	42.55	STD	40
			10.31	198.5	53.09	-	60
			12.70	193.7	64.64	XS	80
			15.09	188.9	75.92	-	100
			18.26	182.6	90.44	-	120
			20.62	177.8	100.93	-	140
			22.23	174.6	107.93	XXS	-
			23.01	173.1	111.27	-	160
10	250	273.1 (10.75)	6.35	260.3	41.76	-	20
			7.80	257.5	51.01	-	30
			9.27	254.5	60.29	STD	40
			12.70	247.7	81.53	XS	60
			15.09	242.9	95.98	-	80
			18.26	236.5	114.71	-	100
			21.44	230.2	133.01	-	120
			25.40	222.3	155.10	XXS	140
			28.58	215.9	172.27	-	160

NPS: ASME term. ⊕ DN: SI Metric term.
API and BS 1600 are dimensionally similar to ASME B36.10

All dimensions are nominal

COMMON PIPE SIZES

DIMENSIONS SHOWN ARE TO ASME B36.10

Nominal Size		Outside Diameter mm (inch)	Wall Thickness mm	Inside Diameter mm	Plain End Mass kg/m	Identification				
NPS	⊕ DN					Standard (STD) X-Strong (XS) XX-Strong (XXS)	Schedule Number			
12	300	323.9 (12.75)	6.35	311.1	49.71	-	20			
			8.38	307.1	65.19	-	30			
			9.53	304.8	73.86	STD	-			
			10.31	303.2	79.71	-	40			
			12.70	298.5	97.44	XS	-			
			14.27	295.3	108.93	-	60			
			17.48	288.9	132.05	-	80			
			21.44	281.0	159.87	-	100			
			25.40	273.1	186.92	XXS	120			
			28.58	266.7	208.08	-	140			
			33.32	257.2	238.69	-	160			
			14	350	355.6 (14.00)	6.35	342.9	54.69	-	10
7.92	339.8	67.91				-	20			
9.53	336.6	81.33				STD	30			
11.13	333.3	94.55				-	40			
11.91	331.8	100.95				-	-			
12.70	330.2	107.40				XS	-			
15.09	325.4	126.72				-	60			
19.05	317.5	158.11				-	80			
23.83	307.9	194.98				-	100			
27.79	300.0	224.66				-	120			
31.75	292.1	253.58				-	140			
35.71	284.2	281.72				-	160			
16	400	406.4 (16.00)	6.35	393.7	62.65	-	10			
			7.92	390.6	77.83	-	20			
			9.53	387.4	93.27	STD	30			
			12.70	381.0	123.31	XS	40			
			16.66	373.1	160.13	-	60			
			21.44	363.5	203.54	-	80			
			26.19	354.0	245.57	-	100			
			30.96	344.5	286.66	-	120			
			36.53	333.3	333.21	-	140			
			40.49	325.4	365.38	-	160			
			18	450	457 (18.00)	6.35	444.5	70.57	-	10
						7.92	441.4	87.71	-	20
9.53	438.2	105.17				STD	-			
11.13	434.9	122.38				-	30			
12.70	431.8	139.16				XS	-			
14.27	428.7	155.81				-	40			
19.05	419.1	205.75				-	60			
23.83	409.5	254.57				-	80			
29.36	398.5	309.64				-	100			
34.93	387.4	363.58				-	120			
39.67	377.9	408.28				-	140			
45.24	366.7	459.39				-	160			

Nominal Size		Outside Diameter mm (inch)	Wall Thickness mm	Inside Diameter mm	Plain End Mass kg/m	Identification				
NPS	⊕ DN					Standard (STD) X-Strong (XS) XX-Strong (XXS)	Schedule Number			
20	500	508 (20.00)	6.35	495.3	78.56	-	10			
			9.53	489.0	117.15	STD	20			
			12.70	482.6	155.13	XS	30			
			15.09	477.8	183.43	-	40			
			20.62	466.8	247.84	-	60			
			26.19	455.6	311.19	-	80			
			32.54	442.9	381.55	-	100			
			38.10	431.8	441.52	-	120			
			44.45	419.1	508.15	-	140			
			50.01	408.0	564.85	-	160			
			22	550	559 (22.00)	6.35	546.1	86.55	-	10
						9.53	539.8	129.14	STD	20
12.70	533.4	171.10				XS	30			
22.23	514.4	294.27				-	60			
28.58	501.7	373.85				-	80			
34.93	489.0	451.45				-	100			
41.28	476.2	527.05				-	120			
47.63	463.5	600.67				-	140			
53.98	450.8	672.30				-	160			
24	600	610 (24.00)				6.35	596.9	94.53	-	10
						9.53	590.6	141.12	STD	20
						12.70	584.2	187.07	XS	-
			14.27	581.1	209.65	-	30			
			17.48	574.6	255.43	-	40			
			24.61	560.4	355.28	-	60			
			30.96	547.7	442.11	-	80			
			38.89	531.8	547.74	-	100			
			46.02	517.6	640.07	-	120			
			52.37	504.9	720.19	-	140			
			59.54	490.5	808.27	-	160			
			26	650	660 (26.00)	7.92	644.6	127.36	-	10
9.53	641.4	152.88				STD	-			
28	700	711 (28.00)	12.70	635.0	202.74	XS	20			
			7.92	695.4	137.32	-	10			
30	750	762 (30.00)	9.53	692.2	164.86	STD	-			
			12.70	685.8	218.71	XS	20			
36	900	914 (36.00)	15.88	679.5	271.23	-	30			
			7.92	746.2	147.29	-	10			
42	1050	1067 (42.00)	9.53	743.0	176.85	STD	-			
			12.70	736.6	234.68	XS	20			
48	1200	1219 (48.00)	15.88	730.2	292.20	-	30			
			7.92	898.6	176.97	-	10			
54	1350	1368 (54.00)	9.53	895.4	212.57	STD	-			
			12.70	889.0	282.29	XS	20			
60	1500	1524 (60.00)	15.88	882.6	351.73	-	30			
			19.05	876.3	420.45	-	40			
72	1800	1827 (72.00)	9.53	1047.8	248.53	STD	-			
			12.70	1041.4	330.21	XS	-			

NPS: ASME term. ⊕ DN: SI Metric term.

All dimensions are nominal

NOTE: API and BS 1600 are dimensionally similar to ASME B36.10

FORMULA TO ATTAIN APPROXIMATE MASS IN KILOGRAMS PER METRE (kg/m) FOR STEEL ROUND PIPE AND TUBING

$$M = (D - T) T \times 0.02466$$

- Where: **m** = mass to the nearest 0.01 kg/m.
D = Outside Diameter in millimetres (mm).
 (To nearest 0.1mm for O.D. up to 406.4mm)
 (To nearest 1.0mm for O.D. 457mm and above)
t = Wall Thickness to nearest 0.01mm

EXAMPLE

NOMINAL SIZE: NPS-12. DN-300

O.D. = 323.9mm W.T. = 9.53mm

Step 1. 323.9 - 9.53 = 314.37

Step 2. 314.37 x 9.53 = 2995.9461

Step 3. 2995.9461 x 0.02466 = **73.88 kg/m**